



## HK UMP40 Submachine Gun Specifications

<b>Caliber:</b>	.40 S&W
<b>Operating Principle:</b>	Simple blowback firing from a closed bolt position
<b>Modes of Fire:</b>	1) Semi-automatic only 2) Semi-automatic & 2-round burst 3) Semi-automatic & fully automatic 4) Semi-automatic, 2-round burst & fully automatic
<b>Cyclic Rate of Fire:</b>	745 rounds per minute
<b>Feed Device:</b>	30-round polymer box magazine
<b>Sights:</b>	Modular. Adjustable iron sights with flip-up peep and U-shaped apertures. Detachable MIL-STD-1913 (Picatinny) rails for attachment of optional targeting devices.
<b>Rifling:</b>	6X polygonal, right hand twist, 1 turn/14.90 inches
<b>Lengths:</b>	
* <b>Barrel:</b>	7.87 inches
* <b>Sight Radius:</b>	12.80 inches
* <b>Overall:</b>	27.17 inches with buttstock extended 33.86 inches with buttstock extended and sound suppressor attached 17.72 inches with buttstock folded 24.41 inches with buttstock folded and sound suppressor attached
<b>Width:</b>	2.50 inches
<b>Height:</b>	11.93 inches with iron sights and magazine
<b>Weights:</b>	
* <b>Overall (without magazine):</b>	4.63 pounds
* <b>Magazine, empty:</b>	.38 pounds
* <b>Carrying Sling:</b>	.22 pounds
* <b>Sound Suppressor (B&amp;T):</b>	.84 pounds
<b>Muzzle Velocity:</b>	1,175 feet per second (Winchester 180 grain JHP) 1,260 feet per second (Cor-Bon 150 grain JHP +P)