





The HK433/HK437 weapon platform

With the weapon platform's integrated concept, we have pursued a systems approach that comprehensively increases the capabilities of its users. This includes calibre-independent uniformity of weapon operation based on the preferred weapon operating mode, an increase in interoperability options, improvement of training, service and maintenance concepts as well as overall greater system safety. The weapon is available in three colours: Onyx Black, Dark Flat Earth and Sniper Grey.



Ammunition overview

300. BLK (7.62 mm x 35) - supersonic ammunition


					Muzzle velocity -v _s - and muzzle energy -E _s -	
Manufacturer	Designation / bullet type	Weight (g)	Grain (gr.)	Intended purpose / comments	HK437 7 "	HK437 9"
Hornady	GMX TAP Expanding fully jacketed bullet	7.2	110	Employment / Fiocchi non-toxic priming compound	600 m/s 1295 J	630 m/s 1410 J
RUAG	Swiss P HV Styx Action Deformation bullet full metal jacket, hollow point, lead core	8.4	130	Insert	560 m/s 1325 J	580 m/s 1420 J
MEN	LFI - Lead-Free Indoor Full metal jacket bullet	9.5	146/147	Training Non-toxic priming compound	475 m/s 1070 J	495 m/s 1170 J
MEN	FMJ (VMWK) / Ball Full metal jacket bullet with lead core	9.5	146/147	Insert Low-emission	515 m/s 1261 J	540 m/s 1400 J
MEN	QD - Quick Defence Lead-free expanding fully jacketed bullet	7,8	120	Insert Lead-free bullet	535 m/s 1115 J	560 m/s 1225 J


Figures rounded off. Ammunition tested and approved.

300. BLK (7.62 mm x 35) - subsonic ammunition

					and muzzle energy -E ₅ -	
Manufacturer	Designation / bullet type	Weight (g)	Grain (gr.)	Intended purpose / comments	HK437 7°	HK437 9"
Hornady	Sub-X Expanding fully jacketed bullet	12.4	190	Employment / Fiocchi non-toxic priming compound	280 m/s 480 J	290 m/s 520 J
RUAG	Swiss P Target OTM jacketed lead core	14.3	220	Insert Non-toxic priming compound	280 m/s 555 J	285 m/s 580 J

Figures rounded off. Ammunition tested and approved.







Modular in application.

For situation-oriented threat scenarios using ballistic protective helmets, we offer two other buttstock options. The first is our tactical helmet buttstock for use with ballistic helmets with a short protective visor. It features a detachable and height-adjustable cheek rest, and is also length-adjustable. It can be folded down to the right against the receiver as required.

The second option is our dedicated helmet buttstock. It is geometrically designed for protective helmets that are equipped with a long protective visor. The helmet buttstock is also length-adjustable, but as a special feature, it can also be folded to the left or to the right. In this case, its end position is below the receiver. The pistol grip and trigger remain within easy reach.

Tactical helmet buitstock






Helmet buttstock





Technical data







HK437	7"	9"
Buttstock	Standard	Standard
muzzle	Flash hider	Flash hider
Calibre	300 BLK (7.62 mm x 35)	300 BLK (7.62 mm x 35)
Operating principle	indirect gas-operated – short stroke piston	indirect gas-operated - short stroke piston
Locking system	Locked rotating bolt head	Locked rotating bolt head
Magazine capacity	10/20/30 cartridges	10/20/30 cartridges
Cartridge case ejection	Right	Right
Modes of fire	Single fire / sustained fire	Single fire / sustained fire
Trigger pull	approx. 30 - 40 N	approx. 30 - 40 N
Rate of fire	approx. 850 rounds/minute	approx. 850 rounds/minute
Barrel profile / twist	Groove/land profile with 4 grooves, 8"/203 mm right-hand twist	Groove/land profile with 4 grooves, 8"/203 mm right-hand twist
Dimensions		
Length (min./max.) (A/B)	approx. 487/745 mm	approx. 537/795 mm
Width (min./max.) (C/D)	approx. 73/106 mm	approx. 73/106 mm
Height 1 (E)	approx. 242 mm	approx. 242 mm
Barrel length 2 (F)	178 mm	229 mm
Sight radius (G)	332 mm	332 mm
Buttstock adjustment travel (H)	84 mm, 7 locking positions	84 mm, 7 locking positions
Cheek rest adjustment travel (I)	21 mm, 4 locking positions	21 mm, 4 locking positions
Weights		
Weapon	approx. 3130 g ₃	approx. 3230 g ₃
Magazine HK PM Gen3 .3004	approx. 179 g	арргох. 179 g

[,] with 30-cartridge magazine, rear sight folded down I 2 without flash hider I 3 weapon with back-up sight, without magazine, without suppressor I 2 PM Gen3 .300 empty weight

Overview of highlights

Fully modular weapon platform for even greater flexibility of individual equipment combinations, including options and cross-functional weapon combinations	luding
Compact weapon dimension comparable with dimensions of classic submachine guns such as the MP5/MP5 S	SD
Cross-calibre standard operating concept with selectable G36/MP5 or HK416/AR-15 operating mod	ies
Higher range compared to 9 mm submachine guns with increased penetration performance on the tar	get
Highly ergonomic weapon design by means of user-oriented arrangement of all operating elements weapon components adaptable to the human physique. The exchangeable lower receiver defines the desired operating concept, thus reducing the training requirement of the shooter	
Precision barrel made from long-lasting, cold-hammered special steel	
M-LOK® and HKey handguards available in different lengths with a range of profile combination and suppressor cover options	i
Chamber Check Marker serves as visual check aid of bolt group position to reduce additional stress factors threatening situations	in
Non-reciprocating charging handle which decouples when the bolt group is running, also serves as forward reversible left/right without tools	assist,
With the appropriate gas adjustment, it can fire both supersonic and subsonic ammunition, and idea without using the gas adjustment as "emergency option"	ally
Highest possible degree of component uniformity within the different calibres to increase efficiency i logistical processes of replenishment, spare parts stocking, repair and training costs	in
Sneaker is specially for low-noise employment as a medium-range weapon for police forces or as a weapon for special forces	specia
Proven to be capable of withstanding barrel obstructions as per NATO-AC225/D14 with defined type ammunition	es of
Drop safety tested in accordance with NATO-AC225/D14	

With regard to the data in this catalogue:

These refer to the time of publication of this catalogue. Products are under continuous development. For this reason, the product may have undergone changes—since publication of this document. We reserve the right to make changes in design or shape as well as deviations in colour. The illustrations may also contain accessories and special equipment that are not part of the standard scope of supply. Colour deviations may occur due to technical reasons.

Drop safety, barrel obstruction capability, over-the-beach-capability and temperature band were tested in accordance with NATO-AC225/D14. Information regarding malfunction rate, system and barrel service life, precision and cook-off is derived from test weapons and HK laboratory results. Depending on the type of ammunition used, deviating cleaning or regular replacement intervals, environmental influences and the condition of the weapon, deviations from the values given may occur in practice. The data do not refer to a single weapon and are not automatically part of a subsequent individual offer, but serve solely for general comparative purposes between different weapon types. Only the data relating to a product which is included in a later individual offer from H&K are binding.

Heckler & Koch GmbH V001.05.2022



Heckler & Koch GmbH

Heckler & Koch-Str. 1 | 78727 Oberndorf a. N., Germany

Tel: +49 (0)742379-0 | Fax: +49 (0)742379-2350

hkinfoboard@heckler-koch-de.com | www.heckler-koch.com